

EC-CERTIFICATE OF CONFORMITY

0432 –CPD – 0023

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21 December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive - CPD), amended by the Directive 93/68/EEC of the Council of European Communities of 22 July 1993, it has been stated that the construction product

Panic exit devices Abloy

Panic exit devices operated by a horizontal bar for single and double leaf doors
as detailed on appendix 2,

placed on the market by

Abloy Oy
Wahlforssinkatu 20
80101 Joensuu
Finland

and produced in the factory:

see appendix 1

submitted by the manufacturer to a factory production control and to the further testing of samples taken at the factory in accordance with a prescribed test plan and that the approved body – 0432 *MPA NRW* - has performed the initial type-testing for the relevant characteristics of the product, the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.

This certificate attests that all provisions concerning the attestation of conformity and the performances described in Annex ZA of the standard

DIN EN 1125 : 2008-04
(EN 1125:2008 (D))

were applied and that the product fulfils all the prescribed requirements.

This certificate was first issued on 19. February 2010 remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Dortmund, 12. September 2012



Dipl.-Ing. H. Jansen
head of the certification body

Panic exit devices Abloy

manufacturing plants

| product | production plant |
|---------|--|
| locks | Abloy Oy Wahlforssinkatu 20 FIN-80101 Joensuu Finland |
| bars | ASSA ABLOY Sicherheitstechnik GmbH Werk Albstadt Bildstockstr. 20 D-72458 Albstadt Germany DO 30.04 |
| | ----- |
| | JPM SAS 40, route de Paris F-03021 Moulins France DO 30.05 |
| | ----- |
| | TESA TALLERES DE ESCORIAZA, S.A. Barrio Ventas 35 E-20305 Irun Spain DO 30.06 |
| | ----- |
| | HEWI Heinrich Wilke GmbH Hagenstrasse 2 D-34454 Bad Arolsen-Mengershausen Germany DO 30.10 |



MATERIALPRÜFUNGSAMT NORDRHEIN-WESTFALEN


Panic exit devices in accordance to EN 1125 for single leaf and double leaf doors

named:

Panic exit devices Abloy

Single leaf door locks

| Item no. | VS-type | function | Backset | Entraxe | Forend width | Classification | | | | | | | | | | Stg |
|----------------|---------|-------------|--------------------------|--------------------|-------------------|----------------|---|---|---|---|--------------|---|---|---|---|---------|
| | | | | | | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | |
| EL060 EL062 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL066 EL068 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL160 EL162 | B | Funktion I | 55 - 100mm 55 - 100mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL166 EL168 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| MP165 | B | Funktion I | 50 mm | 70mm PZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL165 | B | Funktion I | 50 mm | 70mm PZ | 25mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL260 EL262 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL266 EL268 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL360 EL362 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL366 EL368 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL418 EL419 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL420 EL422 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL426 EL428 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| MP418 MP419 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| MP420 MP422 | B | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL460 EL462 | B | Funktion II | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL466 EL468 | B | Funktion II | 30 – 45mm | 92mm PZ 94mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL518 EL519 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL520 EL522 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL526 EL528 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| MP518 MP519 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| MP520 MP522 | B | Funktion I | 55 - 100mm | 72mm PZ 74mm RZ | 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL524 MP524 | B | Funktion I | 50mm | 70mm PZ | 25mm 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |
| EL560 EL562 | B | Funktion II | 55 - 100mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1 - 5 |
| EL566 EL568 | B | Funktion II | 55 - 100mm | 72mm PZ 74mm RZ | 24mm | 3 | 7 | 6 | B | 1 | ³ | 2 | 1 | A | B | 1, 2, 3 |
| EL564 MP564 | B | Funktion II | 50mm | 70mm PZ | 25mm 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | B | 1, 2, 3 |



Double leaf door locks

| Item no. | VS-type | function | Backset | Entraxe | Forend width | Classification | | | | | | | | | | Stg |
|----------------|---------|-------------|-------------|--------------------|---------------|----------------|---|---|---|---|---|---|---|---|---|------|
| | | | | | | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | |
| PE060 PE062 | A | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| PE260 PE262 | A | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| PE420 PE422 | A | Funktion I | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| PE460 PE462 | A | Funktion II | 30 – 45mm | 92mm PZ 94mm RZ | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| LE945 | C | Funktion I | 35mm | - | ³ 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | C | 1, 2 |
| PE160 PE162 | A | Funktion I | 55 – 100 mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| PE360 PE362 | A | Funktion I | 55 – 100 mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| PE520 PE522 | A | Funktion I | 55 – 100 mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| PE560 PE562 | A | Funktion II | 55 – 100 mm | 72mm PZ 74mm RZ | 20mm, 24mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | A | 1, 2 |
| LE955 | C | Funktion I | 100mm | - | 28mm | 3 | 7 | 6 | B | 1 | 3 | 2 | 1 | A | C | 1, 2 |

All kinds of cylinders do not have influence on the escape function of the lock.

function I: constantly working escape door function. Opening is always possible over the handle.

function II: splitted follower, constantly working escape door function from the inside. Opening is always possible over the interior handle from the inside. The external handle will be coupled by an electronically device.

VS-type A: lock for a single or a double leaf door: active or inactive leaf.

VS-type B: lock for a single leaf door.

VS-type C: lock for a double leaf door: only inactive leaf.

Stg: indicates the combination between the lock and the panic bar

Stg (Horizontal Bars)

| no. | manufacturer | Item no.. | coding |
|-----|--------------|---|----------|
| 1 | effeff | 8000-00-1100 (-) 8000-10-1100 (PZ) 8000-11-1100 (RZ) | DO 30.04 |
| 2 | | 8000-00-1100 (-) 8000-20-1100 (PZ) 8000-21-1100 (RZ) | |
| 3 | JPM SAS | NORMA 990000-XX-0A 990100-XX-0A 990001-XX-0A 991000-XX-0A 991100-XX-0A 991001-XX-0A 991101-XX-0A | DO 30.05 |
| 4 | TESA | UNIVERSAL SERIE 19709G9xx | DO 30.06 |
| 5 | HEWI | HEWI PS 160XA 40° HEWI PS 160XA 40° | DO 30.10 |

Outside handle

Outside handles in accordance with DIN 18273 with conformity certificate may be used.